

Model Name			SD-220H2	SD-260H2	SD-300H2	SD-220B2	SD-260B2	SD-300B2
<b>Heat Source</b>	Category	-	Husk furnace			Kerosine or Diesel		
	Type	-	-			Gun type		
	Combustion amount	-	-			24.5-49L/h		
	Boiler capacity	t/h	-			-		
	Boiler pressure	MPa	-			-		
<b>Handling Capacity (Paddy 560g/litter)</b>	Maximum	kg	22,000	26,000	30,000	22,000	26,000	30,000
	Minimum	kg	4,000					
<b>Net weight</b>		kg	5,900	6,200	6,500	5,900	6,200	6,500
<b>Filled weight</b>		kg	27,900	32,200	36,500	27,900	32,200	36,500
<b>Dimensions</b>	Length	mm	4,490					
	Width	mm	4,700					
	Height	mm	10,730	11,930	13,130	10,730	11,930	13,130
<b>Blower Type</b>		-	Diagonal flow fan / Belt driven type					
<b>Voltage</b>		-	3 Phase 220(440)V-60Hz , 380V-50Hz					
<b>Required Power</b>	Blower	kW	4.0					
		kW	4.0					
	Lower screw	kW	1.5					
	Bucket elevator	kW	2.2					
	Upper screw	kW	1.5					
	Dust exhauster	kW	0.1					
	Operation panel	kW	0.05					
	Shutter drum	kW	0.20					
	Moisture sensor	kW	0.015					
	Suction blower	kW	5.5			-		
	Damper	kW	0.015			-		
	Adjuster	kW	0.006			-		
	Burner	kW	-			0.40		
	Sum	kW	<b>19.09</b>			<b>13.97</b>		
	<b>Performance</b>	Loading speed	t/h	30				
Unloading speed		t/h	22					
Loading time		min	44	52	60	44	52	60
Unloading time		min	63	73	83	63	73	83
Drying rate		%/h	0.9~1.3	0.8~1.3	0.7~1.3	0.7~0.9		
<b>Necessary heat quantit</b>		kcal/h	280,000	310,000	340,000	-	-	-
		kW	330	360	400	-	-	-